



## caproBox™

### UV Light and Cooling Device

#### Introduction

The caproBox™ is specifically developed for UV photo cross-linking of samples during caprotec's™ CCMS process. The instrument combines timed UV irradiation and temperature control in one system and allows a convenient, safe, and reproducible utilization of photo cross-linking of CCMS samples. The following features make it ideally suited for the CCMS process:

- Up to 96 samples in standard reaction tubes can be irradiated simultaneously
- Precise temperature control of the samples within 0 °C to 4 °C during irradiation
- Adjustment of the irradiation time possible
- Automatic shut down of UV irradiation when protection cover is opened
- Benchtop, space saving design
- Easy and intuitive to operate



caproBox™ (110 V)

#### Overview

The caproBox™ is used for the cross-linking of affinity bound proteins to Capture Compounds™. During this process, the photoreactive group of the Capture Compound is activated and covalently binds to the targeted proteins. Constant cooling of the samples prevents damage and denaturation of proteins and enables a gentle UV irradiation.

## Technical Specifications

### Power Supply

|                    |  |
|--------------------|--|
| Nominal voltage:   | 230 V (1-5010-001)<br>110 V (1-5010-003) |
| Nominal frequency: | 50 Hz (1-5010-001)<br>60 Hz (1-5010-003) |
| Nominal power:     | 150 W                                    |

### Hardware protection

|          |   |
|----------|---|
| Fusible: | inactive, 2 A/250 V, 5 x 20 mm<br>breaking capacity 1,5 kA at 250 V ~<br>and ohmic load, ceramic tube with<br>extinguishing agent |
|----------|---|

### Electrical Safety

|                        |   |
|------------------------|---|
| Protection class I:    | IEC/EN 61010-1<br>VDE 0411-1  |
| Interference emission: | IEC/EN 61326-1 /2006<br>IEC/EN 55022 Class B  |
| Interference immunity: | IEC/EN 61000-3-2.12:2003<br>+ A2/02.05<br>IEC 61000-3-3:1995 + A1/06.01<br>+ A2/11.05 |

### Environmental conditions

|                        |                               |
|------------------------|-------------------------------|
| Operating temperature: | 0 °C\32 °F to +30 °C\86 °F    |
| Storage temperature:   | -10 °C\14 °F to +50 °C\122 °F |
| Rel. humidity:         | max. 75 %                     |

### Mechanical specifications

|                    |  |
|--------------------|--|
| Mechanical Rating: | IP 20 EN 60529/Type 1 (NEMA)                 |
| Dimensions:        | 280 x 380 x 145 mm (W x D x H;<br>w/o stand) |

### UV Light

|                   |                               |
|-------------------|-------------------------------|
| Electrical power: | 3 x 9 W                       |
| Wavelength:       | 310 nm                        |
| Irradiance:       | $I_e \geq 10 \text{ mW/cm}^2$ |

### Autotimer

|                   |                   |
|-------------------|-------------------|
| Irradiation time: | max. 10 h         |
| Accuracy:         | $\pm 1 \text{ s}$ |

### Thermoblock

|                   |           |
|-------------------|-----------|
| Cooling capacity: | max. 70 W |
| Nominal current:  | 8 A       |
| Nominal voltage:  | 12 V      |

**WEEE-Reg.-Nr. DE 16045286**

## Ordering information

|                                       |             |            |
|---------------------------------------|-------------|------------|
| caproBox™ UV Light and Cooling Device |             |            |
| Item number:                          | 220 V/50 Hz | 1-5010-001 |
|                                       | 110 V/60 Hz | 1-5010-003 |

## Contact

### Headquarters

**caprotec bioanalytics GmbH**  
 Volmerstrasse 5  
 D-12489 Berlin  
 Phone: +49 30 63 92 39 90  
 Fax: +49 30 63 92 39 89  
 Web: [www.caprotec.com](http://www.caprotec.com)  
 Email: [sales@caprotec.com](mailto:sales@caprotec.com)

### caprotec Inc., USA

**caprotec Inc.**  
 15 New England Executive Office Park  
 Burlington, MA 01803, USA  
 Phone: + 1 781 685 4992  
 Fax: +1 781 685 4601  
 Web: [www.caprotec.com](http://www.caprotec.com)  
 E-Mail: [info@caprotec.com](mailto:info@caprotec.com)

### Copyright

© 2008-2010 caprotec bioanalytics GmbH. All rights reserved. Reproduction in whole or in part only with permission of caprotec bioanalytics GmbH.

### Trademarks

caproBox, caprotec, caproBeads, caproMag, caproKit, ImproMed, and Capture Compound are trademarks of caprotec bioanalytics GmbH. All other used tradenames or trademarks belong to their respective owners.